KRM-700M
LED Operating Lamp
(Mobile Type)



Diameter of dome	500mm
Illumination	120,000lux
Color temperature adjustment	3000-5000K
Color indication index	⩾95Ra
Spot diameter	180-300mm
Illumination-adjustment range	10-100%
Power supply	220/110V
Frequency	50/60Hz
Temperature rise at surgeon's head	⩽1° C
Average service Life	50,000hrs
Optional	Emergency battery



KRM-700700
LED Operating Lamp

Diameter of lamp head	700mm/500mm
Light intensity at 1m distance	40K-180K Lux /40K-160K Lux
Color temperature	4000-5000K
Color rendering index	⩾95%
Light field diameter	120-280mm /120-250mm

Illuminance depth	⩾1300mm
Light source	Osram LED chips
LED chips qty	80+48
Height for installation	2.7-3.0m
Low ceiling height design	2.5-2.7m
Power transforme	AC110-220V/50Hz

KRM-700700
LED Operating Lamp



Diameter of lamp head	700mm/ 700mm
Light intensity at 1m distance	40K-180K Lux /40K-180KLux
Color temperature	4000-5000K
Color rendering index Ra	⩾95%
Light field diameter	120-280mm /120-280mm

Illuminance depth	⩾1300mm
Light source	Osram LED
chips LED chips qty	80+80
Height for installation	2.7-3.0m
Power transforme	AC110-220V/50H

KRM-700
LED Operating Lamp

Diameter of lamp head	700mm
Light intensity at 1m distance	40K-180K Lux
Color temperature	4000-5000K
Color rendering index	95%
Light field diameter	120-280mm
Illuminance depth	⩾1300mm
Light source	Osram LED chips
LED chips qty	80
Height for installation	2.7-3.0m
Low ceiling height design	2.5-2.7m
Power transforme	AC110-220V/50Hz

